

SECTION 01580

PROJECT IDENTIFICATION AND SIGNS

PART 1 GENERAL

1.01 REQUIREMENTS INCLUDED

- A. Furnish, install and maintain project identification sign.
- B. Provide temporary on-site informational signs to identify key elements of construction facilities.
- C. Remove signs on completion of construction.
- D. Allow no other signs to be displayed.

1.02 RELATED REQUIREMENTS

- A. Section 01010: Summary of Work
- B. Section 01510: Temporary Utilities
- C. Section 01570: Traffic Regulation

1.03 PROJECT IDENTIFICATION SIGN

- A. One painted sign, of not less than 32 square feet area, with painted graphic content to include:
 - 1. Title of Project
 - 2. Name of Owner
 - 3. Names and titles of Owner's officials
 - 4. Names and titles of:
 - a. Engineer
 - b. Professional Consultants
 - 5. Prime Contractor
 - 6. Major Subcontractors
 - 7. Funding Agency, if other than Owner
- B. Graphic design, style of lettering, and colors: As designated by Project Engineer and approved by Planning Department.
- C. Erect on the site at a lighted location of high public visibility, adjacent to main entrance to site, as approved by permit.

1.04 INFORMATIONAL SIGNS

- A. Painted signs with painted lettering, or standard products.
 - 1. Size of signs and lettering: as required by regulatory agencies, or as appropriate to usage.
 - 2. Colors: as required by regulatory agencies, otherwise of uniform colors throughout Project.
- B. Erect at appropriate locations to provide required information.

1.05 QUALITY ASSURANCE

- A. Sign Painter: Professional Experience in type of work required.
- B. Finishes, Painting: Adequate to resist weathering and fading for scheduled construction period.

PART 2 PRODUCTS

2.01 SIGN MATERIALS

- A. Structure and Framing: May be new or used, wood or metal, in sound condition structurally adequate to work and suitable for specified finish.
- B. Sign Surfaces: Exterior softwood plywood with medium density overlay, standard large sizes to minimize joints.
 - 1. Thickness: As required by standards to span framing members, to provide even, smooth surface without waves or buckles.
- C. Rough Hardware: Galvanized
- D. Paint: Exterior quality.
 - 1. Use Bulletin colors for graphics.
 - 2. Colors for structure, framing, sign surfaces and graphics: As selected by Engineer.

PART 3 EXECUTION

3.01 PROJECT IDENTIFICATION SIGN

- A. Paint exposed surfaces of supports, framing and surface material; one coat of primer and one coat of exterior paint.
- B. Paint graphics in styles, sizes and colors selected.

3.02 INFORMATIONAL SIGNS

- A. Paint exposed surfaces: one coat of primer and one coat of exterior paint.

- B. Paint graphics in styles, sizes and colors selected.
- C. Install at a height for optimum visibility, on ground-mounted poles or attached to temporary structural surfaces.

3.03 MAINTENANCE

- A. Maintain signs and supports in a neat, clean condition; repair damages to structure, framing or sign.
- B. Relocate information signs as required by progress of the work.

3.04 REMOVAL

- A. Remove signs, framing, supports and foundations at completion of project.

END OF SECTION